

# LUBRIPLATE<sup>®</sup> CLEARPLEX-2



## The *Clear Choice* For all your Food Machinery Lubrication

Introducing Lubriplate CLEARPLEX, the clear choice for advanced food machinery lubrication. This colorless, pure USP white mineral oil based, aluminum complex grease is manufactured with ingredients that comply with FDA regulation 21 CFR 178.3570. It is recommended for use in applications where incidental food contact is possible.

- Safe for use on all types of food processing, canning and bottling machinery.
- Engineered for use in plain and anti-friction bearings.
- Provides outstanding anti-wear and anti-corrosion protection.
- Exceptional water resistance.

Call today and find out more about this new food grade grease from Lubriplate. The use of Lubriplate Food Grade Lubricants can eliminate lubrication as a critical control point in any HACCP program.

---

Manufactured with ingredients that comply with FDA regulation 21 CFR 178.3570 for lubricants with incidental contact with the edible product.  
\*NSF H-1 Registration Pending.

---

**LUBRIPLATE<sup>®</sup>**  
*Advancing the Science of Lubrication!*

# LUBRIPLATE®

# CLEARPLEX-2

Food Machinery Lubricant

LUBRIPLATE CLEARPLEX-2 is an Aluminum Complex thickened, USP White Oil-based, food grade grease. It is manufactured with ingredients that comply with FDA 21 CFR 178.3570 and USDA Class H-1 requirements. LUBRIPLATE CLEARPLEX-2 grease is engineered for use in plain and anti-friction bearings in the food-processing industry. It provides outstanding performance in beverage processing machinery such as seamers and closers. Excellent anti-wear, anti-oxidation and water-resistant properties.

LUBRIPLATE PRODUCT	GREASE TYPE	NLGI GRADE	WORKED PENETRATION @77°F / 25°C	BASE OIL TYPE	OIL VIS SUS@100°F	ASTM DROP POINT	COLOR
CLEARPLEX-2	ALUMINUM COMPLEX	2	280	USP FDA 21 CFR 172.878	500	450°F / 232°C	Translucent

Manufactured with ingredients that comply with FDA regulation 21 CFR 178.3570 for lubricants with incidental contact with the edible product.

\*NSF H-1 Registration Pending.

### Features

- Aluminum Complex Base
- Water-Resistant
- Corrosion Protection
- Wear Protection
- FDA ingredient-compliant

### Benefits

- Superior Mechanical Stability
- Less Washout
- Resistant to Acids
- Longer Bearing Life
- Product and Consumer Safety

Packaging Available	Part Number
35-lb Pail	L0351-035
120-lb Drum	L0351-039
400-lb Drum	L0351-040
14.5 oz. Cartridge (40 Per Case)	L0351-098

**This new modern formulated grease from LUBRIPLATE replaces....**

- Amoco FG #2
- Bel-Ray No Tox Clear Grease #2
- Hasco Crystal FM #2
- Jax Clear Guard FM #2
- Keystone Nevastane HT/AW #2
- Lyondell Ideal FG #2
- Mobil FM-102
- Tribology Tech-Lube T-FGG WR #2

**Lubriplate Division / Fiske Brothers Refining Company.**  
Newark, NJ 07105 / Toledo, OH 43605 / Phone 1-800-733-4755  
www.lubriplate.com or e-mail at: info@lubriplate.com

