



Product No.	Size	Description	Ctn. Qty.	Back Pressure P.S.I.	Feet of Head
-------------	------	-------------	-----------	----------------------	--------------

SINGLE-SIZE TEST-BALL® PLUGS

- Made of natural rubber for excellent expansion and memory
- Seals both round and out-of-round pipe
- Zinc-plated steel chain and ring handle acts as an anchor to prevent plug from sliding down a line
- Fits easily through test tees, sanitary tees, floor drains, and other "tight" situations
- Broader expansion range than mechanical plugs



270 008	3/4"-1-1/4"	Test-Ball® Plug	6	17 PSI	40 FT
270 016	1-1/4"-1-1/2"	Test-Ball® Plug	6	13 PSI	30 FT
270 024	2"	Test-Ball® Plug	6	13 PSI	30 FT
270 108	2-1/2"	Test-Ball® Plug	6	13 PSI	30 FT
270 032	3"	Test-Ball® Plug	6	13 PSI	30 FT
270 040	4"	Test-Ball® Plug	6	13 PSI	30 FT
270 059	5"	Test-Ball® Plug	6	13 PSI	30 FT
270 067	6"	Test-Ball® Plug	6	13 PSI	30 FT

BULK TEST-BALL® PLUGS*

- Made of natural rubber for excellent expansion and memory
- Fits easily through test tees, sanitary tees, floor drains, and other "tight" situations
- Seals both round and out-of-round pipe
- Zinc-plated steel chain and ring handle acts as an anchor to prevent plug from sliding down a line
- Broader expansion range than mechanical plugs



240 018	1-1/4"-1-1/2"	Test-Ball® Plug	24	13 PSI	30 FT
240 028	2"	Test-Ball® Plug	24	13 PSI	30 FT
240 038	3"	Test-Ball® Plug	24	13 PSI	30 FT
240 048	4"	Test-Ball® Plug	24	13 PSI	30 FT

* Bulk Test-Ball® Plugs MUST be ordered in quantities of 24 plugs.

SINGLE-SIZE TEST-BALL® PLUGS (UNDERGROUND)

- Designed to block sewer flow or for use as a back plug for sewer air testing
- Natural rubber material for excellent expansion and memory
- Seals both round and out-of-round pipe
- Removable inflation valve offers simple replacement options with quick disconnect fittings and easy repair if damaged
- Feature an eye-bolt for use with a poly-lift line



041 386	8"	Test-Ball® Plug	1	17 PSI	40 FT
041 394	10"	Test-Ball® Plug	1	17 PSI	40 FT
041 408	12"	Test-Ball® Plug	1	17 PSI	40 FT

MULTI-SIZE TEST-BALL® PLUGS

- One size fits multiple pipe diameters, doing the job of 2+ single-size plugs
- Seals both round and out-of-round pipe
- Use to block flow (water DWV test) or as a back plug for sewer air testing
- Zinc-plated steel chain and ring handle acts as an anchor to prevent plug from sliding down a line



276 128	1-1/4"-2"	Test-Ball® Plug	6	17 PSI	40 FT
276 238	2"- 3"	Test-Ball® Plug	6	17 PSI	40 FT
276 348	3"- 4"	Test-Ball® Plug	6	17 PSI	40 FT
276 468	4"- 6"	Test-Ball® Plug	6	17 PSI	40 FT

MULTI-SIZE TEST-BALL® PLUGS (UNDERGROUND)

- One plug fits multiple pipe diameters
- Made of natural rubber, sealing both round and out-of-round pipe
- Use to block flow or as a back plug for sewer air testing
- Removable inflation valve (plugs 8" and larger) offers simple replacement options with quick disconnect fittings and easy repair if damaged



275 048	4"- 6"	Test-Ball® Plug	1	17 PSI	40 FT
275 058	6"- 8"	Test-Ball® Plug	1	17 PSI	40 FT
275 088	8"- 12"	Test-Ball® Plug	1	11 PSI	25 FT
275 128	12"- 18"	Test-Ball® Plug	1	11 PSI	25 FT

CLEAN-SEAL® PLUGS

- Thread into test tee, eliminating test water back splash
- Removable sniffer valve inflation fitting is replaceable
- Made from long-lasting, natural rubber
- Seals both cast-iron and plastic pipe



271 508	1-1/2"	Clean-Seal® Plug	6	13 PSI	30 FT
271 705	2"	Clean-Seal® Plug	6	13 PSI	30 FT
271 713	3"	Clean-Seal® Plug	6	13 PSI	30 FT
271 721	4"	Clean-Seal® Plug	6	13 PSI	30 FT
271 758	6"	Clean-Seal® Plug	1	13 PSI	30 FT

LONG TEST-BALL® PLUGS

- Designed for waste stack testing from floor drain to sewer pipe
- Includes 3' extension hose, ring, and chain assembly
- Long enough to seal wye vertical riser and sewer run
- Ring and chain assembly prevents plug from sliding down a line



271 020	2"	Long Test-Ball® Plug	1	13 PSI	30 FT
271 039	3"	Long Test-Ball® Plug	1	13 PSI	30 FT
271 047	4"	Long Test-Ball® Plug	1	13 PSI	30 FT
271 055	5"	Long Test-Ball® Plug	1	13 PSI	30 FT
271 063	6"	Long Test-Ball® Plug	1	13 PSI	30 FT
271 098	4"-6"	Long Test-Ball® Plug	1	13 PSI	30 FT



Product No.	Size	Description	Ctn. Qty.	Back Pressure P.S.I.	Feet of Head
MS2® LONG TEST-BALL® PLUGS					
<ul style="list-style-type: none"> Designed for waste stack testing from floor drain to sewer pipe Multi-stage deflation eliminates backplash Pressure relief valve to safeguard against over-inflation Long enough to seal wye vertical riser and sewer run Works in multiple pipe diameters Nylon strap and safety handle prevents plug from sliding down a line 					
274 518	2"- 3"	MS2® Plug	1	13 PSI	30 FT
274 526	3"- 4"	MS2® Plug	1	13 PSI	30 FT
274 534	4"- 6"	MS2® Plug	1	13 PSI	30 FT



SINGLE-SIZE MUNI-BALL® PLUGS (UNDERGROUND)					
<ul style="list-style-type: none"> Works in all types of pipe Durable natural rubber construction seals the roughest of surfaces Threaded aluminum bypass Easily converts to an air test plug with use of a conversion kit 					
262 008	1-1/2"	Muni-Ball® Plug	1/8" Bypass	1	22 PSI 50FT
262 010	2"	Muni-Ball® Plug	1/8" Bypass	1	22 PSI 50FT
262 021	3"	Muni-Ball® Plug	3/4" Bypass	1	22 PSI 50FT
262 048	4"	Muni-Ball® Plug	3/4" Bypass	1	22 PSI 50FT
262 064	6"	Muni-Ball® Plug	1-1/2" Bypass	1	13 PSI 30FT
262 080	8"	Muni-Ball® Plug	3" Bypass	1	13 PSI 30FT
262 110	10"	Muni-Ball® Plug	3" Bypass	1	13 PSI 30FT
262 129	12"	Muni-Ball® Plug	3" Bypass	1	13 PSI 30FT
262 137	15"-16"	Muni-Ball® Plug	3" Bypass	1	13 PSI 30FT
262 188	18"	Muni-Ball® Plug	4" Bypass	1	13 PSI 30FT
262 218	21"	Muni-Ball® Plug	4" Bypass	1	13 PSI 30FT
262 242	24"	Muni-Ball® Plug	4" Bypass	1	13 PSI 30FT



MULTI-SIZE MUNI-BALL® PLUGS (UNDERGROUND)					
<ul style="list-style-type: none"> Work in all types of pipe Durable natural rubber construction seals the roughest of surfaces Threaded aluminum bypass Easily converts to an air test plug with the use of a conversion kit One plug fits multiple pipe diameters 					
265 048	4"- 6"	Muni-Ball® Plug	3/4" Bypass	1	17 PSI 40FT
265 068	6"- 8"	Muni-Ball® Plug	1-1/2" Bypass	1	17 PSI 40FT
265 078	8"- 10"	Muni-Ball® Plug	2" Bypass	1	17 PSI 40FT
265 098	8"- 12"	Muni-Ball® Plug	2" Bypass	1	17 PSI 40FT
265 128	12"- 18"	Muni-Ball® Plug	4" Bypass	1	13 PSI 30FT



REPLACEMENT RING & CHAIN ASSEMBLIES					
<ul style="list-style-type: none"> Replacement assemblies for Test-Ball plugs Rings prevent test plugs from sliding down a line Includes a safety tag 					
059 708	2"	Ring with 12" Chain		1	
059 718	3"	Ring with 12" Chain		1	
059 728	4"	Ring with 12" Chain		1	
059 738	5"	Ring with 12" Chain		1	
059 748	6"	Ring with 12" Chain		1	
059 758	2"	Ring with 24" Chain		1	
059 768	3"	Ring with 24" Chain		1	
059 778	4"	Ring with 24" Chain		1	
059 788	5"	Ring with 24" Chain		1	
059 798	6"	Ring with 24" Chain		1	



ECON-O-PUMP® TEST PUMPS					
<ul style="list-style-type: none"> Economical pump for inflating Test Balls Features 0-140 PSI gauge with protective cover All-steel construction for durability 					
273 888		Econ-O-Pump Test Pump		6	

AIR- MAX® TEST PUMPS					
<ul style="list-style-type: none"> Gauge raised from base for protection Durable steel barrel Textured steel base prevents feet from slipping Durable, no-kink hose 					
273 958		Air-Max® Test Pump		1	
034 588		Replacement Hose Assembly w/ Thumb Lock		1	



AIR- MAX® TEST PUMPS					
<ul style="list-style-type: none"> Large barrel for maximum volume means fewer strokes to inflate plug 0-60 PSI gauge for most accurate plug pressure readings All-metal thumb lock for durability Hose strain relief to transfer tension from hose to the barrel Forged steel barrel for extra toughness Large, three-point base for maximum stability Rubber cover to protect gauge from damage Solid wood handle for greater comfort and durability Durable, no-kink hose 					
273 968		Air-Max® Pro HV Test Pump		1	
055 728		Replacement Hose Assembly w/ Thumb Lock		1	

Category 1 Inflatable Test Plugs & Related

11



Product No.	Size	Description	Ctn. Qty.	Back Pressure P.S.I.	Feet of Head
-------------	------	-------------	-----------	----------------------	--------------

EXTENSION HOSES

- Recommended for use with plugs up to 15"
- Ideal for plumbing applications
- Standard tire fitting connections
- 3/16" ID hose



274 011	2'	Extension Hose	6		
274 038	3'	Extension Hose	6		
274 054	5'	Extension Hose	6		
274 100	10'	Extension Hose	1		
274 208	20'	Extension Hose	1		

055 816		Deflator with Clamp (Female Replacement End)	1		
055 808		Inflator with Clamp (Male Replacement End)	1		

274 218	5'	Extension Hose w/ Gauge	1		
274 228	10'	Extension Hose w/ Gauge	1		
274 238	20'	Extension Hose w/ Gauge	1		

POLY-LIFT LINE WITH GAUGE

- Dump valve for quick deflation
- Utilizes quick disconnects
- Poly rope protects hose
- Ideal for plugs 8" and up
- Retard gauge protects against "peg out"
- 3/8" ID hose
- Snap hook connects to plug eyebolt



261 398	20'	Poly-Lift Line / Inflation Hose w/ Gauge	1		
261 408	30'	Poly-Lift Line / Inflation Hose w/ Gauge	1		
261 418	40'	Poly-Lift Line / Inflation Hose w/ Gauge	1		
048 468	0-160 PSI	Retard Gauge w/ Cover	1		
053 458	0-160 PSI	Retard Gauge	1		



POLY-LIFT LINE

- Standard tire fitting connections
- Poly rope protects hose
- Ideal for plugs 8" and up
- 3/16" ID hose
- Snap hook connects to plug eyebolt

261 084	20'	Poly-Lift Line / Inflation Hose	1		
261 106	30'	Poly-Lift Line / Inflation Hose	1		
261 114	40'	Poly-Lift Line / Inflation Hose	1		

TEST GAUGES

- Features 2" unbreakable plastic face
- All connections constructed of high-quality brass
- Inflator valve is replaceable



000 698		0-15 psi w/out test body	1		
000 628		0-30 psi w/out test body	1		
000 638		0-60 psi w/out test body	1		
000 648		0-100 psi w/out test body	1		



024 568		0-15 psi w/ hex test body	1		
019 698		0-30 psi w/ hex test body	1		
019 708		0-60 psi w/ hex test body	1		
019 718		0-100 psi w/ hex test body	1		

000 658		Hex Test Body, 1/8th Tap	1		
068 527		Replacement Snifter Valve 1/8"	1		