

Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	-------------	-----------------	----------

### PVC CEMENTS

#### PVC HEAVY DUTY CLEAR CEMENT

- Heavy-bodied clear cement for PVC pipe and fittings. Up to 12" diameter for Sch. 40 and Sch. 80.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water and DWV.
- Recommended application temperature 40°F to 110°F.
- Thick formula fill gaps in large diameter pipe and loose fitting joints.
- Meets ASTM D-2564.

30850	4 oz.	PVC Heavy Duty Clear	038753-308500	24	9
30863	8 oz.	PVC Heavy Duty Clear	038753-308630	24	16
308630	8 oz.	PVC Heavy Duty Clear - 40 Pack	038753-308630	40	16
30876	16 oz.	PVC Heavy Duty Clear	038753-308760	24	29
30876D	16 oz.	PVC Heavy Duty Clear - Display	038753-308760	24	29
31008	32 oz.	PVC Heavy Duty Clear	038753-310084	12	29
310086	32 oz.	PVC Heavy Duty Clear - 6 Pack	038753-310084	6	14.5
31011	Gallon	PVC Heavy Duty Clear - Wide Mouth Can	038753-310114	6	54



#### LO-V.O.C. PVC HEAVY DUTY CLEAR CEMENT • Meets California and other environmental district rules.

31850	4 oz.	LO-V.O.C. PVC Heavy Duty Clear	038753-318509	24	9
31851	8 oz.	LO-V.O.C. PVC Heavy Duty Clear	038753-318516	24	16
31852	16 oz.	LO-V.O.C. PVC Heavy Duty Clear	038753-318523	24	29
31853	32 oz.	LO-V.O.C. PVC Heavy Duty Clear	038753-318530	12	29



#### PVC MEDIUM CLEAR CEMENT

- Medium-bodied clear cement for use on PVC pipe and fittings. Up to 6" diameter for Sch. 40 and Sch. 80.
- Recommended application temperature 40°F to 110°F.
- Recommended for all grades and types of PVC pipe and fittings, drain, waste, vent pipe, and potable water.
- Meets ASTM D-2564.

31017	4 oz.	PVC Medium Clear	038753-310176	24	9
31017D	4 oz.	PVC Medium Clear - Display	038753-310176	72	9
31018	8 oz.	PVC Medium Clear	038753-310183	24	15
310180	8 oz.	PVC Medium Clear - 40 Pack	038753-310183	40	16
31019	16 oz.	PVC Medium Clear	038753-310190	24	28
31019D	16 oz.	PVC Medium Clear - Display	038753-310190	24	28
31020	32 oz.	PVC Medium Clear	038753-310206	12	27
310206	32 oz.	PVC Medium Clear - 6 Pack	038753-310206	6	40
31021	Gallon	PVC Medium Clear	038753-310213	6	50



#### LO-V.O.C. PVC MEDIUM CLEAR CEMENT • Meets California and other environmental district rules.

31845	4 oz.	LO-V.O.C. PVC Medium Clear	038753-318455	24	9
31845D	4 oz.	LO-V.O.C. PVC Medium Clear - Display	038753-318455	72	9
31846	8 oz.	LO-V.O.C. PVC Medium Clear	038753-318462	24	15
31847	16 oz.	LO-V.O.C. PVC Medium Clear	038753-318479	24	28
31847D	16 oz.	LO-V.O.C. PVC Medium Clear - Display	038753-318479	24	28
318460	16 oz.	LO-V.O.C. PVC Medium Clear - 40 Pack	038753-318462	40	25
31848	32 oz.	LO-V.O.C. PVC Medium Clear	038753-318486	12	27
318486	32 oz.	LO-V.O.C. PVC Medium Clear - 6 Pack	038753-318486	6	27
31849	Gallon	LO-V.O.C. PVC Medium Clear	038753-318493	6	50



#### PVC REGULAR CLEAR CEMENT

- Regular-bodied clear cement for use on PVC pipe and fittings. Up to 4" for DWV Sch. 40 and up to 2" for Sch. 80.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water and DWV.
- Sets up quickly.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

31012	4 oz.	PVC Regular Clear	038753-310121	24	8
31012D	4 oz.	PVC Regular Clear - Display	038753-310121	72	8
31013	8 oz.	PVC Regular Clear	038753-310138	24	15
310131	8 oz.	PVC Regular Clear - 40 Pack	038753-310138	40	16
31014	16 oz.	PVC Regular Clear	038753-310145	24	28
31014D	16 oz.	PVC Regular Clear - Display	038753-310145	24	28
31015	32 oz.	PVC Regular Clear	038753-310152	12	27
31016	Gallon	PVC Regular Clear	038753-310169	6	50





Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
<b>LO-V.O.C. PVC REGULAR CLEAR CEMENT</b> • Meets California and other environmental district rules.					
31840	4 oz.	LO-V.O.C. PVC Regular Clear	038753-318400	24	8
31841	8 oz.	LO-V.O.C. PVC Regular Clear	038753-318417	24	15
318411	8 oz.	LO-V.O.C. PVC Regular Clear - 40 Pack	038753-318417	40	25
31842	16 oz.	LO-V.O.C. PVC Regular Clear	038753-318424	24	28
31842D	16 oz.	LO-V.O.C. PVC Regular Clear - Display	038753-318424	24	28
31843	32 oz.	LO-V.O.C. PVC Regular Clear	038753-318431	12	27
31844	Gallon	LO-V.O.C. PVC Regular Clear	038753-318448	6	50



### PVC REGULAR CLEAR ADVANCED CEMENT

- Regular-bodied clear cement for use on PVC pipe and fittings. Up to 4" for DWV Sch. 40 and up to 2" for Sch. 80.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water and DWV.
- Sets up quickly.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

31925	4 oz.	PVC Regular Clear Advanced	038753-319254	24	8
31926	8 oz.	PVC Regular Clear Advanced	038753-319261	24	15
31927	16 oz.	PVC Regular Clear Advanced	038753-319278	24	28
31928	32 oz.	PVC Regular Clear Advanced	038753-319285	12	27
31929	Gallon	PVC Regular Clear Advanced	038753-319292	6	50



### PVC HEAVY DUTY GRAY CEMENT

- Heavy-bodied gray colored cement for use on PVC pipe and fittings. Up to 12" diameter for Sch. 40 and Sch. 80.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water and DWV.
- Thick formula fills gaps in large diameter pipe and fittings.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

31093	4 oz.	PVC Heavy Duty Gray	038753-310930	24	9
31094	8 oz.	PVC Heavy Duty Gray	038753-310947	24	16
31095	16 oz.	PVC Heavy Duty Gray	038753-310954	24	31
31105	32 oz.	PVC Heavy Duty Gray	038753-311050	12	29
31118	Gallon	PVC Heavy Duty Gray - Wide Mouth Can	038753-311180	6	54



### LO-V.O.C. PVC HEAVY DUTY GRAY CEMENT

 • Meets California and other environmental district rules.

31860	4 oz.	LO-V.O.C. PVC Heavy Duty Gray	038753-318608	24	9
31861	8 oz.	LO-V.O.C. PVC Heavy Duty Gray	038753-318615	24	15
31862	16 oz.	LO-V.O.C. PVC Heavy Duty Gray	038753-318622	24	31
31863	32 oz.	LO-V.O.C. PVC Heavy Duty Gray	038753-318639	12	29
318636	32 oz.	LO-V.O.C. PVC Heavy Duty Gray - 6 Pack	038753-318639	6	14
31864	Gallon	LO-V.O.C. PVC Heavy Duty Gray	038753-318646	6	51



### PVC HEAVY DUTY GRAY FAST SET CEMENT

- Very heavy-bodied medium-setting gray colored cement for use on PVC pipe and fittings. Up to 18" diameter for Sch. 40 and Sch. 80.
- Formulated for quick installation of irrigation pipe and fittings.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water and DWV.
- Builds up for large diameter installations.
- Fill gaps in large diameter pipe and loose fitting joints.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

31121	16 oz.	PVC Heavy Duty Gray Fast Set	038753-311210	24	27
31122	32 oz.	PVC Heavy Duty Gray Fast Set	038753-311227	12	28
31123	Gallon	PVC Heavy Duty Gray Fast Set Wide Mouth Can	038753-311234	6	50



### LO-V.O.C. PVC HEAVY DUTY GRAY CEMENT - INDUSTRIAL GRADE

- Heavy bodied cement for use on pressure industrial systems, drain, waste and vent pipe.
- No special techniques required.
- Resistant to caustics and hypochlorites up to 15% solution.
- INDUSTRIAL GRADE.
- For Sch. 40 and Sch. 80 PVC, Types I and II up to 12" diameter.
- Meets ASTM D-2564.

31113	16 oz.	LO-V.O.C. PVC Heavy Duty Gray	038753-311135	24	30
31114	32 oz.	LO-V.O.C. PVC Heavy Duty Gray	038753-311142	12	29
31115	Gallon	LO-V.O.C. PVC Heavy Duty Gray - Wide Mouth Can	038753-311159	6	50

Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	-------------	-----------------	----------

### PVC MEDIUM GRAY CEMENT

- Medium-bodied gray colored cement for use on PVC pipe and fittings. Up to 6" diameter for Sch. 40 and Sch. 80.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water and DWV.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

30883	4 oz.	PVC Medium Gray	038753-308838	24	9
30883D	4 oz.	PVC Medium Gray - Display	038753-308838	72	9
30884	8 oz.	PVC Medium Gray	038753-308845	24	15
30885	16 oz.	PVC Medium Gray	038753-308852	24	29
30886	32 oz.	PVC Medium Gray	038753-308869	12	28
30887	Gallon	PVC Medium Gray	038753-308876	6	50



### LO-V.O.C. PVC MEDIUM GRAY CEMENT • Meets California and other environmental district rules.

31865	4 oz.	LO-V.O.C. PVC Medium Gray	038753-318653	24	9
31865D	4 oz.	LO-V.O.C. PVC Medium Gray - Display	038753-318653	72	27
31866	8 oz.	LO-V.O.C. PVC Medium Gray	038753-318660	24	15
31867	16 oz.	LO-V.O.C. PVC Medium Gray	038753-318677	24	29
31868	32 oz.	LO-V.O.C. PVC Medium Gray	038753-318684	12	28
31869	Gallon	LO-V.O.C. PVC Medium Gray	038753-318691	6	50



### PVC RAIN-R-SHINE® BLUE CEMENT

- Medium-bodied blue colored cement for PVC pipe and fittings. Up to 6" diameter.
- Very fast-setting cement formulated for wet conditions and/or quick pressurization and fast installation.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water and DWV.
- Both Sch. 40 and Sch. 80.
- Pool/Irrigation.
- Recommended application temperature 40°F to 110°F.
- No primer needed on non-pressure DWV, up to 4" where local codes permit.
- Meets ASTM D-2564.

30890	4 oz.	PVC Rain-R-Shine® Blue	038753-308906	24	9
30891	8 oz.	PVC Rain-R-Shine® Blue	038753-308913	24	16
308910	8 oz.	PVC Rain-R-Shine® Blue - 40 Pack	038753-308913	40	26
30893	16 oz.	PVC Rain-R-Shine® Blue	038753-308937	24	28
30893D	16 oz.	PVC Rain-R-Shine® Blue - Display	038753-308937	24	28
30894	32 oz.	PVC Rain-R-Shine® Blue	038753-308944	12	28
308946	32 oz.	PVC Rain-R-Shine® Blue - 6 Pack	038753-308944	6	14
30895	Gallon	PVC Rain-R-Shine® Blue - Wide Mouth Can	038753-308951	6	50



### LO-V.O.C. PVC RAIN-R-SHINE® BLUE CEMENT • Meets California and other environmental district rules.

31855	4 oz.	LO-V.O.C. PVC Rain-R-Shine® Blue	038753-318554	24	9
31856	8 oz.	LO-V.O.C. PVC Rain-R-Shine® Blue	038753-318561	24	16
318560	8 oz.	LO-V.O.C. PVC Rain-R-Shine® Blue - 40 Pack	038753-318561	40	26
31857	16 oz.	LO-V.O.C. PVC Rain-R-Shine® Blue	038753-318578	24	28
31857D	16 oz.	LO-V.O.C. PVC Rain-R-Shine® Blue - Display	038753-318578	24	28
31858	32 oz.	LO-V.O.C. PVC Rain-R-Shine® Blue	038753-318585	12	28
31859	Gallon	LO-V.O.C. PVC Rain-R-Shine® Blue	038753-318592	6	50



### PVC ALL WEATHER CLEAR CEMENT

- Medium-bodied clear cement for use on PVC pipe and fittings. Up to 6" diameter.
- Meets ASTM D-2564.
- No primer needed on non-pressure DWV, up to 4" where local codes permit.
- Recommended for all grades and types of PVC pipe and fittings, potable water and DWV, Sch. 40 and Sch. 80.
- Recommended application temperature of -15°F to 110°F.

31132	16 oz.	PVC All Weather Clear	038753-311326	24	30
31132D	16 oz.	PVC All Weather Clear - Display	038753-311326	24	30
31133	32 oz.	PVC All Weather Clear	038753-311333	12	29
31135	Gallon	PVC All Weather Clear - Wide Mouth Can	038753-311357	6	50





Product No.	Size	Description	UPC Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	----------	-----------------	----------

### ALL PURPOSE CEMENT

- Medium-bodied milky clear cement for ABS, PVC, or CPVC up to 6" diameter.
- Recommended for pipe and fittings Sch. 40 and Sch. 80, potable water and DWV.
- Recommended application temperature 40°F to 110°F.
- Meets performance requirements of ASTM D-2564, D-2235, F-493.
- Check local codes for acceptability of this product.

30818	4 oz.	All Purpose Cement	038753-308180	24	9
30818D	4 oz.	All Purpose Cement - Display	038753-308180	72	27
30821	8 oz.	All Purpose Cement	038753-308210	24	16
308210	8 oz.	All Purpose Cement - 40 Pack	038753-308210	40	26
30834	16 oz.	All Purpose Cement	038753-308340	24	29
30834D	16 oz.	All Purpose Cement - Display	038753-308340	24	24
30847	32 oz.	All Purpose Cement	038753-308470	12	29
30848	Gallon	All Purpose Cement	038753-308487	6	50

### LO-V.O.C. ALL PURPOSE CEMENT • Meets California and other environmental district rules.

31895	4 oz.	LO-V.O.C. All Purpose	038753-318950	24	9
31896	8 oz.	LO-V.O.C. All Purpose	038753-318967	24	15

### PVC FLEXIBLE CLEAR CEMENT

- Medium-bodied clear cement for use on flexible PVC pipe and rigid fittings. Up to 3" diameter.
- Formulated to withstand pressures and vibrations commonly associated with spa and swimming pool installations.
- Meets manufacturer's rated line pressure for flexible PVC pipe.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

30875	4 oz.	PVC Flexible Clear	038753-308753	12	4
30879	32 oz.	PVC Flexible Clear	038753-308791	12	28

### ABS TO PVC TRANSITION GREEN CEMENT

- Medium-bodied green colored cement for use in joining ABS to PVC in non-pressure transition joints.
- All schedules up to 6" diameter pipe and fittings.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-3138.

30900	4 oz.	ABS To PVC Transition Green	038753-309002	24	6
30925	16 oz.	ABS To PVC Transition Green	038753-309255	6	7
30926	32 oz.	ABS To PVC Transition Green	038753-309262	12	28

### LO-V.O.C. ABS TO PVC TRANSITION GREEN CEMENT

- Meets California and other environmental district rules.

31807	16 oz.	LO-V.O.C. ABS To PVC Transition Green	038753-318073	6	7
31808	32 oz.	LO-V.O.C. ABS To PVC Transition Green	038753-318080	12	23

### HANDY PACKS

- Convenient "Handy Pack" for storage – just add pipe and fittings.
- Contains one can of PVC Cement and one can of Primer.

30238	4 oz.	LO-V.O.C. PVC Regular & NSF Purple Primer	038753-302386	12	9
30242	8 oz.	LO-V.O.C. PVC Medium & NSF Purple Primer	038753-302423	20	28
30246	4 oz.	PVC Regular & NSF Purple Primer	038753-302461	12	9
30246D	4 oz.	PVC Regular & NSF Purple Primer - Display	038753-302461	24	18
302480	8 oz.	PVC Regular & NSF Purple Primer - Mini	038753-302485	160	224
30244	8 oz.	PVC Medium & NSF Purple Primer	038753-302447	20	26
30247	8 oz.	LO-V.O.C. PVC Regular & NSF Purple Primer	038753-302478	20	26

Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	-------------	-----------------	----------

### ABS CEMENTS

#### ABS BLACK CEMENT

- Medium-bodied black cement for ABS pipe and fittings. Up to 6" diameter.
- For ALL types and grades of ABS pipe and fittings for DWV.
- For all non-pressure applications.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2235.

30999	4 oz.	ABS Black	038753-309996	24	8
30999D	4 oz.	ABS Black - Display	038753-309996	48	16
30889	8 oz.	ABS Black	038753-308890	24	15
308890	8 oz.	ABS Black - 40 Pack	038753-308890	40	25
30892	16 oz.	ABS Black	038753-308920	24	28
30892D	16 oz.	ABS Black - Display	038753-308920	24	28
30902	32 oz.	ABS Black	038753-309026	12	26
309026	32 oz.	ABS Black - 6 Pack	038753-309026	6	13
30915	Gallon	ABS Black	038753-309156	6	51



#### LO-V.O.C. ABS BLACK CEMENT • Meets California and other environmental district rules.

31800	4 oz.	LO-V.O.C. ABS Black	038753-318004	24	8
31800D	4 oz.	LO-V.O.C. ABS Black - Display	038753-318004	72	27
31801	8 oz.	LO-V.O.C. ABS Black	038753-318011	24	15
318011	8 oz.	LO-V.O.C. ABS Black - 40 Pack	038753-318011	40	25
31802	16 oz.	LO-V.O.C. ABS Black	038753-318028	24	28
31803	32 oz.	LO-V.O.C. ABS Black	038753-318035	12	26
318036	32 oz.	LO-V.O.C. ABS Black - 6 Pack	038753-318035	6	13
31804	Gallon	LO-V.O.C. ABS Black	038753-318042	6	51



#### ABS SPECIAL MILKY CLEAR CEMENT

- For ALL types and grades of ABS pipe and fittings for DWV.
- Fast curing for all non-pressure applications.
- Formulated to eliminate the clean-up problems associated with black ABS cements.
- Medium-bodied milky clear cement for ABS pipe and fittings. Up to 6" diameter.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2235.

30922	16 oz.	ABS Special Milky Clear	038753-309224	24	28
30923	32 oz.	ABS Special Milky Clear	038753-309231	12	27
30924	Gallon	ABS Special Milky Clear	038753-309248	6	51



#### LO-V.O.C. ABS MILKY CLEAR CEMENT • Meets California and other environmental district rules.

31908	32 oz.	LO-V.O.C. ABS Milky Clear	038753-319087	12	27
-------	--------	---------------------------	---------------	----	----



#### ABS EXTRA SPECIAL BLACK CEMENT

- Medium-bodied black cement for use on ABS pipe and fittings. Up to 6" diameter.
- Formulated especially for the hot, arid climates in the Western states.
- For all non-pressure applications.
- For ALL types and grades of ABS pipe and fittings for DWV.
- Meets ASTM D-2235.

30916	4 oz.	ABS Extra Special Black	038753-309163	24	9
30916D	4 oz.	ABS Extra Special Black - Display	038753-309163	72	27
30917	8 oz.	ABS Extra Special Black	038753-309170	24	15
309170	8 oz.	ABS Extra Special Black - 40 Pack	038753-309170	40	25
30918	16 oz.	ABS Extra Special Black	038753-309187	24	28
30919	32 oz.	ABS Extra Special Black	038753-309194	12	27
30920	Gallon	ABS Extra Special Black	038753-309200	6	51





Product No.	Size	Description	UPC Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	----------	-----------------	----------

### CPVC CEMENTS

#### CPVC HEAVY DUTY GRAY CEMENT

- Heavy-bodied gray colored cement for use on CPVC pipe and fittings up to 12" diameter.
- For C.T.S. (copper tube size) and Sch. 80, potable water pressure pipe.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM F-493.

31036	16 oz.	CPVC Heavy Duty Gray	038753-310367	24	29
31037	32 oz.	CPVC Heavy Duty Gray	038753-310374	12	29



#### LO-V.O.C. CPVC HEAVY DUTY GRAY CEMENT - INDUSTRIAL GRADE

- Heavy-bodied cement for use on pressure industrial systems, drain, waste and vent pipe.
- Resistant to caustics and hypochlorites up to 15% solution.
- For Sch. 40 and Sch. 80 CPVC, Type IV up to 12" diameter.
- No special techniques required.
- INDUSTRIAL GRADE.
- Meets ASTM F-493.

31148	16 oz.	LO-V.O.C. CPVC Heavy Duty Gray	038753-311487	24	30
31149	32 oz.	LO-V.O.C. CPVC Heavy Duty Gray	038753-311494	12	29
31150	Gallon	LO-V.O.C. CPVC Heavy Duty Gray - Wide Mouth Can	038753-311500	6	50



#### CPVC MEDIUM ORANGE CEMENT

- Medium-bodied orange colored cement for use on CPVC pipe and fittings. Up to 6" diameter.
- For C.T.S. (copper tube size) and Sch. 80, potable water pressure pipe.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM F-493.

31128	4 oz.	CPVC Medium Orange	038753-311289	24	9
31128D	4 oz.	CPVC Medium Orange - Display	038753-311289	72	27
31129	8 oz.	CPVC Medium Orange	038753-311296	24	16
311290	8 oz.	CPVC Medium Orange - 40 Pack	038753-311296	40	26
31130	16 oz.	CPVC Medium Orange	038753-311302	24	29
31131	32 oz.	CPVC Medium Orange	038753-311319	12	29
31127	Gallon	CPVC Medium Orange	038753-311272	6	51



#### LO-V.O.C. CPVC MEDIUM ORANGE CEMENT • Meets California and other environmental district rules.

31820	4 oz.	LO-V.O.C. CPVC Medium Orange	038753-318202	24	9
31820D	4 oz.	LO-V.O.C. CPVC Medium Orange	038753-318202	72	27
31821	8 oz.	LO-V.O.C. CPVC Medium Orange	038753-318219	24	16
318210	8 oz.	LO-V.O.C. CPVC Medium Orange	038753-318219	24	16
31822	16 oz.	LO-V.O.C. CPVC Medium Orange	038753-318226	24	29



#### LO-V.O.C. CPVC FLOWGUARD GOLD\*\* ALL WEATHER 1-STEP YELLOW CEMENT

- Exceeds new environmental requirements and meets various California district rules.
- May be used without primer where local codes permit.
- For cold water systems and hot water systems up to 180°F.
- Faster cure time/reduced installation time.
- For copper tube size (CTS) CPVC hot and cold potable water pipe and fittings up to 2" diameter interference fit only.
- Meets ASTM F-493.

31910	4 oz.	LO-V.O.C. CPVC Flowguard Gold® 1-Step Yellow	038753-319100	24	9
31911	8 oz.	LO-V.O.C. CPVC Flowguard Gold® 1-Step Yellow	038753-319117	24	16
319110	8 oz.	LO-V.O.C. CPVC Flowguard Gold® 1-Step Yellow - 40 Pack	038753-319117	40	26
31912	16 oz.	LO-V.O.C. CPVC Flowguard Gold® 1-Step Yellow	038753-319124	24	29
31913	32 oz.	LO-V.O.C. CPVC Flowguard Gold® 1-Step Yellow	038753-319131	12	29
31914	Gallon	LO-V.O.C. CPVC Flowguard Gold® 1-Step Yellow	038753-319148	6	54

\*FlowGuard Gold is a registered trademark of the Lubrizol Corporation.

Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	-------------	-----------------	----------

### PRIMERS & CLEANERS

#### PURPLE PRIMER - NSF LISTED

- Purple-tinted aggressive primer for use on PVC and CPVC pipe and fittings.
- Removes surface dirt, grease and grime as well as softens the pipe surface to allow a fast, secure solvent weld.
- For use in areas where plumbing code calls for verification that a primer has been used.
- Meets ASTM F-656.

30755	4 oz.	Purple Primer - NSF Listed	038753-307558	24	8
30755D	4 oz.	Purple Primer - NSF Listed - Display	038753-307558	72	8
30756	8 oz.	Purple Primer - NSF Listed	038753-307565	24	14
307560	8 oz.	Purple Primer - NSF Listed - 40 Pack	038753-307565	40	23
30757	16 oz.	Purple Primer - NSF Listed	038753-307572	24	25
30757D	16 oz.	Purple Primer - NSF Listed - Display	038753-307572	24	25
30758	32 oz.	Purple Primer - NSF Listed	038753-307589	12	24
307586	32 oz.	Purple Primer - NSF Listed - 6 Per	038753-307589	6	24
30759	Gallon	Purple Primer - NSF Listed	038753-307596	6	45



#### LO-V.O.C. PURPLE PRIMER - NSF LISTED • Meets California and other environmental district rules.

31900	4 oz.	LO-V.O.C. Purple Primer - NSF Listed	038753-319001	24	8
31900D	4 oz.	LO-V.O.C. Purple Primer - NSF Listed - Display	038753-319001	72	24
31901	8 oz.	LO-V.O.C. Purple Primer - NSF Listed	038753-319018	24	14
319010	8 oz.	LO-V.O.C. Purple Primer - NSF Listed - 40 Pack	038753-319018	40	27
31902	16 oz.	LO-V.O.C. Purple Primer - NSF Listed	038753-319025	24	25
31902D	16 oz.	LO-V.O.C. Purple Primer - NSF Listed	038753-319025	24	25
31903	32 oz.	LO-V.O.C. Purple Primer - NSF Listed	038753-319032	12	24
319036	32 oz.	LO-V.O.C. Purple Primer - NSF Listed - 6 Pack	038753-319032	6	12
31904	Gallon	LO-V.O.C. Purple Primer - NSF Listed	038753-319049	6	45



#### CLEAR PRIMER - NSF LISTED

- A clear aggressive primer for use on PVC and CPVC pipe and fittings.
- All schedules and all diameters.
- Removes all surface dirt, grease and grime as well as softens pipe in preparation for solvent cement.
- Meets ASTM F-656.

30750	4 oz.	Clear Primer - NSF Listed	038753-307503	24	8
30751	8 oz.	Clear Primer - NSF Listed	038753-307510	24	14
30752	16 oz.	Clear Primer - NSF Listed	038753-307527	24	25
30753	32 oz.	Clear Primer - NSF Listed	038753-307534	12	24
30754	Gallon	Clear Primer - NSF Listed	038753-307541	6	46



#### PURPLE PRIMER/CLEANER

- Purple-tinted all purpose primer/cleaner for PVC and CPVC pipe and fittings.
- Less aggressive than clear primer and purple primer.
- Removes surface dirt, grease and grime as well as softens pipe in preparation for solvent cement.

30780	4 oz.	Purple Primer/Cleaner	038753-307800	24	8
30780D	4 oz.	Purple Primer/Cleaner - Display	038753-307800	72	24
30783	8 oz.	Purple Primer/Cleaner	038753-307831	24	14
307830	8 oz.	Purple Primer/Cleaner - 40 Pack	038753-307831	40	23
30796	16 oz.	Purple Primer/Cleaner	038753-307961	24	25
30806	32 oz.	Purple Primer/Cleaner	038753-308067	12	24
30768	Gallon	Purple Primer/Cleaner	038753-307688	6	46



#### CLEANER

- Clear cleaner for ABS, PVC and CPVC pipe and fittings.
- All schedules and all diameters.
- Flows freely and evaporates quickly.
- Fast-acting cleaner removes surface dirt, grease and grime.

30779	4 oz.	Clear Cleaner	038753-307794	24	8
30779D	4 oz.	Clear Cleaner - Display	038753-307794	72	24
30782	8 oz.	Clear Cleaner	038753-307824	24	14
307820	8 oz.	Clear Cleaner - 40 Pack	038753-307824	40	23
30795	16 oz.	Clear Cleaner	038753-307954	24	26
30805	32 oz.	Clear Cleaner	038753-308050	12	25
308056	32 oz.	Clear Cleaner - 6 Pack	038753-308050	6	12
30766	Gallon	Clear Cleaner - Wide Mouth Cleaner	038753-307664	6	46



Product No.	Size	Description	UPC Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	----------	-----------------	----------

**UNITED ELCHEM PVC CEMENTS**

**PLUMB-TITE™ PVC MEDIUM "HOT" BLUE CEMENT**

- Medium-bodied blue colored cement for PVC pipe and fittings Up to 6" diameter.
- Very fast setting cement formulated for wet conditions and/or quick pressurization and fast installation.
- Recommended for ALL grades and types of PVC pipe and fittings potable water, pressure pipe and DWV.
- Fades to clear in sunlight.
- No primer needed on non-pressure DWV up to 4" diameter, where local codes permit.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

2066S	4 oz.	Plumb-Tite PVC Medium "Hot" Blue	083675-020665	24	9
2056S	8 oz.	Plumb-Tite PVC Medium "Hot" Blue	083675-020566	24	16
2046S	16 oz.	Plumb-Tite PVC Medium "Hot" Blue	083675-020467	24	27
2036S	32 oz.	Plumb-Tite PVC Medium "Hot" Blue	083675-020368	12	26
2024	Gallon	Plumb-Tite PVC Medium "Hot" Blue	083675-020245	6	52


**PLUMB-TITE™ LOW-V.O.C. PVC MEDIUM "HOT" BLUE CEMENT**

- Meets California and other environmental district rules.

200166S	4 oz.	Plumb-Tite PVC Medium "Hot" Blue	083675-220159	24	9
200136S	32 oz.	Plumb-Tite PVC Medium "Hot" Blue	083675-220128	12	26
200124C	Gallon	Plumb-Tite PVC Medium "Hot" Blue	083675-220111	6	52


**TURF-TITE™ PVC MEDIUM "HOT" BLUE CEMENT**

- Medium-bodied blue colored cement for PVC pipe and fittings Up to 6" diameter.
- Very fast setting cement formulated for wet conditions and/or quick pressurization and fast installation.
- Recommended for ALL grades and types of PVC pipe and fittings potable water, pressure pipe and DWV.
- Fades to clear in sunlight.
- No primer needed on non-pressure DWV up to 4" diameter, where local codes permit.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

2466S	4 oz.	Turf-Tite PVC Medium "Hot" Blue	083675-024663	24	9
2456S	8 oz.	Turf-Tite PVC Medium "Hot" Blue	083675-024564	24	16
2446S	16 oz.	Turf-Tite PVC Medium "Hot" Blue	083675-024465	24	27
2436S	32 oz.	Turf-Tite PVC Medium "Hot" Blue	083675-024366	12	26
2424	Gallon	Turf-Tite PVC Medium "Hot" Blue	083675-024243	6	52


**LOW - V.O.C. TURF-TITE™ PVC MEDIUM "HOT" BLUE CEMENT**

- Meets California environmental district rules.

240156S	8 oz.	Low - VOC Turf-Tite Medium "Hot" Blue	083675-240148	24	16
240146S	16 oz.	Low - VOC Turf-Tite Medium "Hot" Blue	083675-240131	24	27
240136S	32 oz.	Low - VOC Turf-Tite Medium "Hot" Blue	083675-240124	12	26
240124C	Gallon	Low - VOC Turf-Tite Medium "Hot" Blue	083675-240117	6	52


**WELL-TITE™ PVC MEDIUM "HOT" BLUE CEMENT**

- Medium-bodied blue colored cement for PVC pipe and fittings Up to 8" diameter.
- Very fast setting cement formulated for wet conditions and/or quick pressurization and fast installation.
- Recommended for ALL grades and types of PVC pipe and fittings potable water, pressure pipe and DWV.
- Fades to clear in sunlight.
- No primer needed on non-pressure DWV up to 4" diameter, where local codes permit.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

3046S	16 oz.	Well-Tite PVC Medium "Hot" Blue	083675-304635	24	27
3036S	32 oz.	Well-Tite PVC Medium "Hot" Blue	083675-303621	12	26
3024	Gallon	Well-Tite PVC Medium "Hot" Blue	083675-302419	6	52



**Product No.**      **Size**      **Description**      **UPC Code**      **Carton Quantity**      **Ctn. Wt.**

**POLAR-WELD™ PVC ALL WEATHER CEMENT**

- Medium-bodied clear cement for use on PVC pipe and fittings.
- Formulated for fast initial set-up at temperatures down to -5°F to 110°F. Sch. 40 and Sch. 80.
- Meets ASTM D-2564.
- Recommended for all grades and types of PVC pipe and fittings, potable water, pressure pipe and DWV.
- No primer needed on non-pressure DWV up to 4" in diameter, where local codes permit.

2666S	4 oz.	Polar-Weld PVC All Weather	083675-026667	24	9
2656S	8 oz.	Polar-Weld PVC All Weather	083675-026568	24	16
2646S	16 oz.	Polar-Weld PVC All Weather	083675-026469	24	27
2636S	32 oz.	Polar-Weld PVC All Weather	083675-026360	12	26
2624	Gallon	Polar-Weld PVC All Weather	083675-026247	6	52



**SUPER 30® #213 WHITE EXTRA HEAVY BODY**

- Very heavy bodied medium-setting white cement for use on PVC pipe and fittings up to 30" diameter.
- Formulated for quick installation.
- Recommended for all grades and types of PVC pipe and fittings, potable water, pressure pipe and DWV.
- Builds up for large diameter installation to fill gaps.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

21336S	32 oz.	#213 White	083675-213326	12	26
--------	--------	------------	---------------	----	----



**SUPER 30® #1800 GRAY EXTRA HEAVY BODY**

- Very heavy bodied medium-setting gray cement for use on PVC pipe and fittings up to 30" diameter.
- Formulated for quick installation.
- Recommended for all grades and types of PVC pipe and fittings, potable water, pressure pipe and DWV.
- Builds up for large diameter installation to fill gaps.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

1846S	16 oz.	# 1800 Gray	083675-018464	24	27
1836S	32 oz.	# 1800 Gray	083675-018365	12	26
1824	Gallon	# 1800 Gray - Wide Mouth Can	083675-018242	6	52



**PVC HEAVY DUTY CLEAR CEMENT**

- Heavy-bodied clear cement for PVC pipe and fittings up to 12" diameter for Sch. 40 and Sch. 80.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water, pressure pipe, conduit and DWV.
- Recommended application temperature 40°F to 110°F.
- Thick formula fills gaps in large diameter pipe and loose fitting joints.
- Meets ASTM D-2564.

1566S	4 oz.	PVC Heavy Duty Clear	083675-015661	24	9
1556S	8 oz.	PVC Heavy Duty Clear	083675-015562	24	14
1546S	16 oz.	PVC Heavy Duty Clear	083675-015463	24	27
1536S	32 oz.	PVC Heavy Duty Clear	083675-015364	12	26
1524	Gallon	PVC Heavy Duty Clear	083675-015241	6	52



**PVC MEDIUM CLEAR CEMENT**

- Medium-bodied clear cement for PVC pipe and fittings up to 6" diameter for Sch. 40 and Sch. 80.
- Recommended application temperature 40°F to 110°F.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water, pressure pipe and DWV.
- Meets ASTM D-2564.

1266S	4 oz.	PVC Medium Clear	083675-012660	24	9
1256S	8 oz.	PVC Medium Clear	083675-012561	24	16
1246S	16 oz.	PVC Medium Clear	083675-012462	24	27
1236S	32 oz.	PVC Medium Clear	083675-012363	12	26
1224	Gallon	PVC Medium Clear	083675-012240	6	52



**PVC REGULAR CLEAR CEMENT**

- Regular-bodied clear cement for PVC pipe and fittings up to 4" diameter for Sch. 40 and up to 2" for Sch. 80.
- Recommended application temperature 40°F to 110°F.
- Sets up quickly.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water, pressure pipe and DWV.
- Meets ASTM D-2564.

2266S	4 oz.	PVC Regular Clear	083675-022669	24	9
2256S	8 oz.	PVC Regular Clear	083675-022560	24	16
2246S	16 oz.	PVC Regular Clear	083675-022461	24	27
2236S	32 oz.	PVC Regular Clear	083675-022362	12	26
2224	Gallon	PVC Regular Clear	083675-022249	6	52





Product No.	Size	Description	UPC Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	----------	-----------------	----------

**PVC REGULAR CLEAR FAST SET CEMENT**

- Regular-bodied clear cement for PVC pipe and fittings up to 4" diameter for Sch. 40 and up to 2" for Sch. 80.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water, pressure pipe and DWV.
- Sets up quickly.

2866S	4 oz.	PVC Regular Clear Fast Set Cement	083675-028661	24	9
2856S	8 oz.	PVC Regular Clear Fast Set Cement	083675-028562	24	16
2846S	16 oz.	PVC Regular Clear Fast Set Cement	083675-028463	24	27
2836S	32 oz.	PVC Regular Clear Fast Set Cement	083675-028364	12	26
2824	Gallon	PVC Regular Clear Fast Set Cement	083675-028241	6	52



**PVC HEAVY DUTY GRAY CEMENT**

- Heavy-bodied gray cement for PVC pipe and fittings up to 12" diameter for Sch. 40 and Sch. 80.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water, pressure pipe and DWV.
- Recommended application temperature 40°F to 110°F.
- Thick formula fills gaps in large diameter pipe and loose fitting joints.
- Meets ASTM D-2564.

1756S	8 oz.	PVC Heavy Duty Gray	083675-017566	24	16
1746S	16 oz.	PVC Heavy Duty Gray	083675-017467	24	27
1736S	32 oz.	PVC Heavy Duty Gray	083675-017368	12	26
1724	Gallon	PVC Heavy Duty Gray - Wide Mouth Can	083675-017245	6	52



**PVC MEDIUM GRAY CEMENT**

- Medium-bodied gray cement for PVC pipe and fittings up to 6" diameter for Sch. 40 and Sch. 80.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water, pressure pipe and DWV.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

1666S	4 oz.	PVC Medium Gray	083675-016668	24	9
1656S	8 oz.	PVC Medium Gray	083675-016569	24	16
1646S	16 oz.	PVC Medium Gray	083675-016460	24	27
1636S	32 oz.	PVC Medium Gray	083675-016361	12	26
1624	Gallon	PVC Medium Gray	083675-016248	6	52



**MULTI PURPOSE CLEAR CEMENT**

- Regular-bodied clear cement for PVC, ABS or CPVC pipe and fittings up to 4" diameter.
- Recommended for pipe and fittings Sch. 40 and Sch. 80, potable water, pressure pipe and DWV.
- Recommended application temperature 40°F to 110°F.
- Meets performance requirements of ASTM D-2564, D-2235, F-493.

6266S	4 oz.	Multi Purpose Regular Clear	083675-062665	24	9
6256S	8 oz.	Multi Purpose Regular Clear	083675-062566	24	16
6246S	16 oz.	Multi Purpose Regular Clear	083675-062467	24	27
6236S	32 oz.	Multi Purpose Regular Clear	083675-062368	12	26
6224	Gallon	Multi Purpose Regular Clear	083675-062245	6	52



**ABS CEMENTS**

**ABS MEDIUM BLACK CEMENT**

- Medium-bodied black cement for ABS pipe and fittings up to 6" diameter.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2235.
- For all non-pressure applications.
- For ALL types and grades of ABS pipe and fittings and DWV.

4466S	4 oz.	ABS Medium Black	083675-044661	24	9
4456S	8 oz.	ABS Medium Black	083675-044562	24	16
4446S	16 oz.	ABS Medium Black	083675-044463	24	27
4436S	32 oz.	ABS Medium Black	083675-044364	12	26
4424	Gallon	ABS Medium Black	083675-044241	6	52



Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
<b>ABS SPECIAL MILKY CLEAR CEMENT</b>					
<ul style="list-style-type: none"> <li>• Medium-bodied milky clear cement for ABS pipe and fittings up to 6" diameter.</li> <li>• Recommended application temperature 40°F to 110°F.</li> <li>• Meets ASTM D-2235.</li> </ul>			<ul style="list-style-type: none"> <li>• Fast curing for or all non-pressure applications.</li> <li>• For All types and grades of ABS pipe and fittings and DWV.</li> </ul>		
4136S	32 oz.	ABS Special Milky Clear	083675-041363	12	26



**CPVC CEMENTS**

**CPVC MEDIUM ORANGE CEMENT**

<ul style="list-style-type: none"> <li>• Medium-bodied orange colored cement for use on CPVC pipe and fittings up to 6" diameter.</li> <li>• For C.T.S. (Copper Tube Size) and Sch. 80, potable water pressure pipe.</li> </ul>			<ul style="list-style-type: none"> <li>• Recommended application temperature 40°F to 110°F.</li> <li>• Meets ASTM F-493.</li> </ul>		
3266S	4 oz.	CPVC Medium Orange	083675-032668	24	9
3256S	8 oz.	CPVC Medium Orange	083675-032569	24	16
3246S	16 oz.	CPVC Medium Orange	083675-032460	24	27
3236S	32 oz.	CPVC Medium Orange	083675-032361	12	26



**PRIMERS & CLEANERS**

**BLUE PRIMER - NSF LISTED**

<ul style="list-style-type: none"> <li>• Blue-tinted aggressive primer for use on PVC and CPVC pipe and fittings.</li> <li>• Blue color fades to clear in direct sunlight.</li> </ul>			<ul style="list-style-type: none"> <li>• Formulated to work with all "TITE" products.</li> <li>• Meets ASTM F-656.</li> </ul>		
8056S	8 oz.	Prime-Tite Blue Primer - NSF Listed	083675-080560	24	16
8046S	16 oz.	Prime-Tite Blue Primer - NSF Listed	083675-080461	24	27
8036S	32 oz.	Prime-Tite Blue Primer - NSF Listed	083675-080362	12	26
8024	Gallon	Prime-Tite Blue Primer - NSF Listed	083675-080249	6	45



**LOW-V.O.C. PURPLE PRIMER - NSF LISTED**

<ul style="list-style-type: none"> <li>• Purple-tinted aggressive primer for use on PVC and CPVC pipe and fittings.</li> <li>• Exceeds new environmental requirements and meets various California district rules.</li> </ul>			<ul style="list-style-type: none"> <li>• For use in areas where plumbing code calls for verification that a primer has been used.</li> <li>• Removes surface dirt, grease and grime as well as softens the pipe surface to allow a fast, secure solvent weld.</li> </ul>		
8766S	4 oz.	LOW-VOC Purple Primer - NSF Listed	083675-087668	24	9
8756S	8 oz.	LOW-VOC Purple Primer - NSF Listed	083675-087569	24	16
8746S	16 oz.	LOW-VOC Purple Primer - NSF Listed	083675-087460	24	27
8736S	32 oz.	LOW-VOC Purple Primer - NSF Listed	083675-087361	12	26
8724	Gallon	LOW-VOC Purple Primer - NSF Listed	083675-087248	6	45
5824	Gallon	LOW-VOC Purple Primer - NSF Listed Wide Mouth Can	083675-058248	6	45



**LOW-VOC CLEAR PRIMER - NSF LISTED**

<ul style="list-style-type: none"> <li>• A clear aggressive primer for use on PVC and CPVC pipe and fittings.</li> <li>• All schedules and all diameters.</li> <li>• Meets ASTM F-656.</li> </ul>			<ul style="list-style-type: none"> <li>• Removes surface dirt, grease and grime as well as softens the pipe surface to allow a fast, secure solvent weld.</li> </ul>		
9366S	4 oz.	LOW-VOC Clear Primer - NSF Listed	083675-093669	24	9
9356S	8 oz.	LOW-VOC Clear Primer - NSF Listed	083675-093560	24	16
9346S	16 oz.	LOW-VOC Clear Primer - NSF Listed	083675-093461	24	27
9336S	32 oz.	LOW-VOC Clear Primer - NSF Listed	083675-093362	12	26
9324	Gallon	LOW-VOC Clear Primer - NSF Listed	083675-093249	6	45



**LOW-VOC PURPLE PRIMER/CLEANER**

<ul style="list-style-type: none"> <li>• Purple-tinted all purpose primer/cleaner for use on PVC and CPVC pipe and fittings.</li> <li>• Removes surface dirt, grease and grime as well as softens the pipe surface to allow a fast, secure solvent weld.</li> </ul>			<ul style="list-style-type: none"> <li>• Less aggressive than clear primer and purple primer.</li> <li>• Exceeds new environmental requirements and meets various California district rules.</li> </ul>		
8866S	4 oz.	LOW-VOC Purple Primer/Cleaner	083675-088665	24	9
8856S	8 oz.	LOW-VOC Purple Primer/Cleaner	083675-088566	24	16
8846S	16 oz.	LOW-VOC Purple Primer/Cleaner	083675-088467	24	27
8836S	32 oz.	LOW-VOC Purple Primer/Cleaner	083675-088368	12	26
8824	Gallon	LOW-VOC Purple Primer/Cleaner	083675-088245	6	45





Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	-------------	-----------------	----------

### LOW - VOC CLEAR CLEANER

- Clear cleaner for ABS, PVC and CPVC pipe and fittings.
- Fast acting cleaner removes surface dirt, grease and grime.
- All schedules and all diameters.
- Flows freely and evaporates quickly.
- Exceeds new environmental requirements and meets various California district rules.

7366S	4 oz.	LOW-VOC Clear Cleaner	083675-073661	24	9
7356S	8 oz.	LOW-VOC Clear Cleaner	083675-073562	24	16
7346S	16 oz.	LOW-VOC Clear Cleaner	083675-073463	24	27
7336S	32 oz.	LOW-VOC Clear Cleaner	083675-073364	12	26
7324	Gallon	LOW-VOC Clear Cleaner	083675-073241	6	45

### ACCESSORIES

#### SOLVENT CEMENT AND PRIMER ACCESSORIES

- Standard replacement daubers specifically sized for 4 oz., 8 oz., 16 oz. and 32 oz. cement/primer cans.
- Standard replacement cans.
- Brush and roller applicator tops for 16 & 32 oz. cans.



31299	4 oz.	Dauber	038753-312996	48	2
31309	8 oz.	Dauber	038753-313092	48	2
31310	16 oz.	Dauber	038753-313108	48	2
31312	32 oz.	Dauber	038753-313122	48	2
31313	16/32 oz.	Dauber for CPVC	038753-313139	48	2
31257	16/32 oz.	Brush top Dauber	038753-312576	48	4
31275	12"	Gallon can roller applicator	038753-312750	12	5
31276	12"	Gallon can swab applicator	038753-312767	12	5
MTC66	4 oz.	Cement Can	038753-313047	24	3
31305	8 oz.	Cement Can	038753-313054	24	3
31306	16 oz.	Cement Can	038753-313061	24	3
31307	32 oz.	Cement Can	038753-313078	12	3
30901	1 Gallon	Wide Mouth Can	038753-309019	6	3



#### ADJUSTABLE DAUBER

- For applying solvent cement and primers.
- Fits can sizes 1/2 pint through quart.
- Specially constructed easy open, easy close sealing controls evaporation of solvents and prevents spillage.
- Dauber is unbreakable.
- Designed to adjust to various can dimensions and allows application of the proper amount of cement to ensure a good solvent weld.

31300		Adjustable plastic dauber w/ 1/2" ball	038753-313009	100	3
31301		Adjustable plastic dauber w/ 1" ball	038753-313016	100	3
31302		Adjustable plastic dauber	038753-313023	50	2



#### CEMENT CARRIER

- Designed to make it easier to keep cement and cleaner ready for use on the job.
- Caddy holds two 32 oz. cans.
- Patented.

31250	32 oz. can	Cement Carrier	038753-312507	12	3
-------	------------	----------------	---------------	----	---