

Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	-------------	-----------------	----------

### PLUMBER'S PUTTY

- Stainless fixture setting compound for setting frames, faucets, strainer baskets, etc.
- Stays flexible and will not crack or shrink.
- Made of easily workable soft, pliable material.
- Not for use on marble, granite, plastic or any other dimensional stone.
- Meets Military Spec. TTP-1536A.

31166	14 oz.	Putty - Plastic container	038753-311661	24	24
31166D	14 oz.	Putty - Plastic container - Display	038753-311661	30	30
311660	14 oz.	Putty - Plastic container - Mini Pallet	038753-311661	270	270
31170	3 lb.	Putty - Plastic container	038753-311708	6	20
31174	5 lb.	Putty - Plastic container	038753-311746	6	32
31174D	5 lb.	Putty - Plastic container - Display	038753-311746	6	32



### PIPE/GASKET LUBE

- Non-toxic, soft, paste like material for lubricating bell joint pipe gaskets.
- Will not deteriorate natural or synthetic rubber.
- Will not support bacteria.
- Dissolves in hot water.

30599	16 oz.	Pipe Lubricant	038753-305998	24	30
30600	32 oz.	Pipe Lubricant	038753-306001	12	25
30601	Gallon	Pipe Lubricant	038753-306018	4	34
30605	5 Gallon	Pipe Lubricant	038753-306056	1	42



### PIPE SEAL

- Caulking lead substitute for sealing cast iron soil pipe joints.
- Air dry putty compound packs easily and resists shrinkage.
- Forms a hard leakproof seal.
- For use whenever it is impractical to pour molten lead.

30614	16 oz.	Pipe Seal	038753-306148	12	20
-------	--------	-----------	---------------	----	----



### GRAY PIPE JOINT COMPOUND

- Non-hardening gray paste seals and lubricates threaded joints.
- For use on water, steam or air lines.
- Non-separating and non-toxic material.
- Not for use on plastic threads.

31226	1 fl. oz.	Gray Pipe Joint Compound	038753-312262	12	2
31226D	1 fl. oz.	Gray Pipe Joint Compound - Display	038753-312262	54	8
31227	4 fl. oz.	Gray Pipe Joint Compound	038753-312279	12	7
31228	8 fl. oz.	Gray Pipe Joint Compound	038753-312286	12	13
31228D	8 fl. oz.	Gray Pipe Joint Compound - Display	038753-312286	30	26
31235	16 fl. oz.	Gray Pipe Joint Compound	038753-312354	24	46
31236	32 fl. oz.	Gray Pipe Joint Compound	038753-312361	12	43



### GREAT WHITE® PIPE JOINT COMPOUND WITH PTFE

- Lubricates and seals all threaded joints.
- White, non-hardening, non-separating, non-toxic paste.
- Withstands up to 3,000 PSI on gases from -50 to +400°F, and 10,000 PSI on liquids from -50 to +500°F.
- For use with water, steam, caustics or dilute acid lines.
- Can be used with plastic and metal threads.

31229	1 fl. oz.	Great White® Pipe Joint Compound w/ PTFE	038753-312293	12	1
31229D	1 fl. oz.	Great White® Pipe Joint Compound w/ PTFE - Display	038753-312293	54	3
312291	1 fl. oz.	Great White® Pipe Joint Compound w/ PTFE - Gravity Feed	038753-312293	120	6
31230	4 fl. oz.	Great White® Pipe Joint Compound w/ PTFE	038753-312309	12	7
31230D	4 fl. oz.	Great White® Pipe Joint Compound w/ PTFE	038753-312309	48	7
31231	8 fl. oz.	Great White® Pipe Joint Compound w/ PTFE	038753-312316	12	12
31231D	8 fl. oz.	Great White® Pipe Joint Compound w/ PTFE	038753-312316	30	12
31232	16 fl. oz.	Great White® Pipe Joint Compound w/ PTFE	038753-312323	24	39
31233	32 fl. oz.	Great White® Pipe Joint Compound w/ PTFE	038753-312330	12	40



### GREAT BLUE® PIPE JOINT COMPOUND

- Flexible blue, non-hardening, non-separating, non-toxic paste, no odor, easy clean-up.
- Use on PVC, CPVC, ABS, polyethylene, polypropylene, iron, steel, copper or brass threads up to and including 2".
- Withstands up to 3,000 PSI on gases from -50° to +400° F and 10,000 PSI on liquids from -50° to +500° F
- ABS, cycolac, polypropylene, iron, steel or copper.
- Lubricates and seals thread on water, natural gas, steam, air lines, caustics and dilute acids.

31265	1 fl. oz.	Great Blue® Pipe Joint Compound	038753-312651	12	2
31261	4 fl. oz.	Great Blue® Pipe Joint Compound	038753-312613	12	7
31262	8 fl. oz.	Great Blue® Pipe Joint Compound	038753-312620	12	12
31263	16 fl. oz.	Great Blue® Pipe Joint Compound	038753-312637	24	39
312636	16 fl. oz.	Great Blue® Pipe Joint Compound	038753-312637	6	10
31264	32 fl. oz.	Great Blue® Pipe Joint Compound	038753-312644	12	40





Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	-------------	-----------------	----------

**WHITE GENERAL PURPOSE THREAD SEAL TAPE WITH PTFE**

- Provides a clean, positive seal on threaded connections.
- A high density product that resists tearing and stretching for easy, efficient application.
- Available carded or packaged bulk on spools.
- Complies with Military Spec. No. T-27730A & UL31RO.
- 3 mils thick, 0.7 grams/cubic centimeter density.

31199	1/2" x 260"	PTFE White Thread Seal Tape	038753-311999	144	6
31202	1/2" x 520"	PTFE White Thread Seal Tape	038753-312026	144	7
31212	3/4" x 260"	PTFE White Thread Seal Tape	038753-312125	144	6


**YELLOW GAS LINE THREAD SEAL TAPE WITH PTFE**

- Manufactured especially for natural gas, propane, butane, water, oil and chemical lines.
- Heavier than white tape with density of 1.35-1.50 grams/cubic centimeters, 4 mils thick.
- Complies with MIL-T22230A (ASG), UL 31 RO, AGA 3226 and CAN/ULC-S642.
- Packaged on spools in convenient dispenser box.

31403	1/2" x 260"	PTFE Yellow Thread Seal Tape - Dispenser pack	038753-314037	100	7
31403D	1/2" x 260"	PTFE Yellow Thread Seal Tape - Display	038753-314037	20	1


**PINK WATER LINE THREAD SEAL TAPE WITH PTFE**

- Provides fast positive seal for water lines, sewage lines and sprinkler systems.
- Effective on metal or plastic threads.
- Complies with MIL-T-27730A.
- Pink tape is 3 mils thick with density of 1.35-1.50 grams/cubic centimeter.
- Packaged on spools in a display carton.

31402D	1/2" x 260"	PTFE Pink Thread Seal Tape - Display	038753-314020	50	3
--------	-------------	--------------------------------------	---------------	----	---


**CLEAR THREAD CUTTING OIL**

- Protection helps make sharp clean threads while extending the life of your dies.
- Formulated for hand thread cutting machines.
- Anti-mist and non-staining formula is not affected by weather.

30200	16 oz.	Clear Cutting Oil (hand threading)	038753-302003	12	13
30201	32 oz.	Clear Cutting Oil (hand threading)	038753-302010	12	26
30202	Gallon	Clear Cutting Oil (hand threading)	038753-302027	6	50


**DARK THREAD CUTTING OIL**

- Formulated for high speed cutting machines.
- A special mixture of sulfonated and chlorinated oils provides high film strength.
- Keeps machines running cooler and extends the life of your dies.
- Anti-mist and non-staining formula is not affected by weather.

30203	16 oz.	Dark Cutting Oil (speed threading)	038753-302034	12	13
30204	32 oz.	Dark Cutting Oil (speed threading)	038753-302041	12	26
30205	Gallon	Dark Cutting Oil (speed threading)	038753-302058	6	50


**ALL PURPOSE LEAK DETECTOR**

- Detects leaks quickly on all types of tubing, valves, cylinders, pressure tanks or other systems under air, gas or oxygen pressure.
- Functions in a -55°F to +160°F temperature range.
- Slow evaporation rate provides longer inspection time.

30209	8 oz.	All Purpose Leak Detector with dauber	038753-302096	12	9
30211	16 oz.	All Purpose Leak Detector with trigger spray	038753-302119	12	17
30212	Gallon	All Purpose Leak Detector	038753-302126	4	39


**PLUMBERS HAND CLEANER**

- Safely removes plastic pipe cements from hands.
- Also removes varnish, enamels, grease and adhesives.
- Use with or without water.
- Freshly scented conditioning formula contains aloe, lanolin, jojoba and vitamin E.

30221	16 oz.	Hand Cleaner - squeeze bottle	038753-302218	12	14
30223	60 oz.	Hand Cleaner - 1/2 gallon w/ dispenser	038753-302232	4	19

Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
<b>EPOXY PUTTY</b>					
		<ul style="list-style-type: none"> <li>Convenient multi-purpose sealing, patching and mending compound.</li> <li>Steel filled material, mixes in the hand and hardens in minutes.</li> </ul>	<ul style="list-style-type: none"> <li>May be drilled, tapped, filed, sanded, sealed and painted when hardened.</li> <li>Non-toxic material contains no solvents and will not shrink.</li> </ul>		
31270	4 oz.	Tube Epoxy Putty - Display	038753-312705	12	8



<b>TUB-N-TILE CAULK</b>					
		<ul style="list-style-type: none"> <li>White, flexible, latex sealant.</li> <li>Fills and seals cracks and joints.</li> <li>For caulking around showers, tubs, lavatories and sinks.</li> <li>Cleans up with soap and water.</li> </ul>	<ul style="list-style-type: none"> <li>Can be used to reset loose tiles.</li> <li>Can be painted when dry with either oil base or latex paint.</li> </ul>		
30240	6 oz.	Tub-N-Tile Caulk - Tube	038753-302409	24	8
30241	10 oz.	Tub-N-Tile Caulk - Cartridge	038753-302416	24	30



<b>TUB-N-TILE ULTRA CLEAR SEALANT</b>					
		<ul style="list-style-type: none"> <li>Applies white and dries clear.</li> <li>Flexible butyl acrylate formula adheres to porous surfaces such as wood and masonry.</li> <li>Cleans up with soap and water.</li> </ul>	<ul style="list-style-type: none"> <li>Flexible material won't crack or peel and adheres tightly.</li> <li>Paintable with no offensive odors.</li> </ul>		
30235	6 oz.	Tub-N-Tile Clear Sealant- Tube	038753-302355	12	6



<b>SILICONE SEALANT</b>					
		<ul style="list-style-type: none"> <li>Clear and white sealants for high performance sealing.</li> <li>Bonds to porcelain, ceramic marble, fiberglass and most metals.</li> <li>Remains permanently elastic.</li> <li>When fully cured, recognized by USDA for use in meat and poultry plants.</li> </ul>	<ul style="list-style-type: none"> <li>Meets Fed. Spec. TT-S-00230C Class A &amp; TT-S-001543A Class A, Mil. Spec. 46106A, ASTM C920, FDA Regulation No. 21 CFR 177.2600.</li> <li>Withstands temperature from -60°F to 400°F.</li> </ul>		
30236	10.3 oz.	Silicone Sealant, Clear - Cartridge	038753-302362	12	11
30237	10.3 oz.	Silicone Sealant, White - Cartridge	038753-302379	12	11



<b>HEAVY DUTY WAX BOWL RING</b>					
		<ul style="list-style-type: none"> <li>100% pure petroleum wax gasket for setting any floor type closet bowl.</li> <li>Fits 3" or 4" waste lines and meets Military Spec. TTP-1536A.</li> </ul>	<ul style="list-style-type: none"> <li>Provides a permanent seal impervious to vermin, odors, gases and acids.</li> </ul>		
31190		Heavy Duty Wax Bowl Ring	038753-311906	48	25



<b>HEAVY DUTY WAX BOWL RING W/ SLEEVE</b>					
		<ul style="list-style-type: none"> <li>100% pure petroleum wax gasket for setting any floor type closet bowl.</li> <li>Fits 3" or 4" waste lines and meets Military Spec. TTP-1536A.</li> </ul>	<ul style="list-style-type: none"> <li>Provides a permanent seal impervious to vermin, odors, gases and acids.</li> <li>Polyethylene sleeve extends discharge opening for a more positive seal assuring proper bowl alignment.</li> </ul>		
31194		Wax bowl ring with polyethylene sleeve	038753-311944	24	15
31193		Flanged gasket w/brass bolts and nuts	038753-311937	24	17



**Oatey**

Category 6 Plumbing Chemicals

6



Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
<b>URETHANE REINFORCED WAX BOWL RING W/ SLEEVE</b>					
<ul style="list-style-type: none"> <li>• 100% pure petroleum wax gasket for setting any floor type closet bowl.</li> <li>• Provides a permanent seal impervious to vermin, odors, gases and acids.</li> <li>• Fits 3" to 4" waste lines and meets Military Spec. TTP-1536A.</li> <li>• Polyethylene sleeve extends discharge opening for a more positive seal assuring proper bowl alignment.</li> <li>• Urethane sponge provides resiliency. Expands and contracts with the bowl or building to prevent wax from settling.</li> </ul>					
31195		Urethane Reinforced Wax Bowl Ring with Polyethylene Sleeve	038753-311951	24	14



<b>MAXWAX® WAX BOWL RING</b>					
<ul style="list-style-type: none"> <li>• 40% thicker wax ring with a polyethylene sleeve to assure a tight seal.</li> <li>• 100% pure petroleum wax gasket for setting any floor type closet bowl.</li> <li>• Fits 3" to 4" waste lines and meets Military Spec. TTP-1536A.</li> <li>• Polyethylene sleeve extends discharge opening for a more positive seal assuring proper bowl alignment.</li> <li>• Provides a permanent seal impervious to vermin, odors, gases and acids.</li> </ul>					
31188		MaxWax Bowl Ring with Sleeve	038753-311883	12	7



<b>URINAL WAX RING</b>					
<ul style="list-style-type: none"> <li>• Urinal wax ring has a urethane sponge to provide resiliency.</li> </ul>					
31187		Urinal Wax Ring	038753-311876	12	3